


AquAtec


waterproofing membrane system that encapsulates expansion joints in floors, walls and roofs

Typical Components

- (1) Concrete slab
- (2) Waterproof membrane epoxy bonded to the substrate either side of the expansion gap
- (3) Expansion joint fitted directly over water barrier and centred over the expansion gap
- (4) Downpipe connected to waterproof membrane
- (5) Waterproof membrane bonded to the sides of the expansion joint and cross-linked to the membrane bonded to the substrate forming a completely watertight envelope




AquAtec 1500 : A01-A02




Expansion Joint Selection Criteria

Product Details

| Joint | Gap | Move | ement | | | Product Dimensions | | | | Product |
|---|----------|---------------|-------------|---------------------|-------------------|--------------------|----------|--------|--------|---------------|
| Location | Width | Capacity (mm) | | Watertight- ness | Dielectric rating | Thick- | Material | Sight- | Block- | Number |
| | B (mm) | ± | [Total] | rating | (mm) | (mm) | A (mm) | C (mm) | | |
| Floor - Floor Floor - Wall Wall - Wall Corner Wall | 25 - 500 | | 100% Gap | FN1928(R) | 2Kv | 1.14 | 325 | - | - | 1500-A01-325 |
| | | | | | | | 500 | | | 1500-A01-500 |
| | | | | | | | 750 | | | 1500-A01-750 |
| | | | | | | | 1000 | | | 1500-A01-1000 |





External & Internal Expansion Joints 25 - 500 mm (1 - 20") Expansion Gaps

Features

Movement

Easy to install

High movement capacity +/- 250mm

Material

1.14mm thick EPDM waterproofing membrane bonded to the substrate and cross-linked to membranes bonded to the side and foot plates of the joint encapsulating the expansion joint

External and Internal Locations


| Floor to Floor | |
|----------------|--|
| Floor to Wall | |
| Wall to Wall | |
| Corner Wall | |
| Roof to Roof | |
| Roof to Wall | |
| Parapet Walls | |

Traffic Frequency per day

| Ż | | | | | |
|---|---|---|---|---|--|
| _ | - | - | - | - | |

System Options

| Gap width(s) | 25-500 mm |
|-------------------------|-----------------------|
| Material width(s) | 325, 500, 750, 1000mm |
| Material thickness | 1.14mm |
| Colour(s) | Black |
| Drainage | Down pipe option |
| Pre-assembly in factory | Contact Vexcolt |



Airport Terminals | Educational | Exhibition Centres |
Department Stores | Distribution & Retail Warehouses |
Factories | Hospitals | Museums | Offices & Hotels |
Parking | Places of Worship | Residential Buildings |
Rail, Metros & Elevated Rail Stations | Roads & Bridges |
Shopping Centres | Sports Stadiums | Supermarkets